



AUTOTRONIC 25 BOOST 230V 12V/24V



Overview

AUTOTRONIC 25 BOOST 230V 12V/24V

cod. 807540

Battery charger with electronic control of the charging current, automatic interruption and restart (TRONIC), for charging lead-acid batteries with 12/24V voltage.

Fit with switches to choose either anormal charge (MIN) or quick charge (BOOST) in the buffer mode (TRONIC) or drooping characteristic mode (CHARGE).

The buffer automatic charge is adequate for maintenance free sealed batteries (GEL/AGM/START-STOP), while the drooping characteristic charge is adequate for free-electrolyte batteries (WET).

Features:

- choice of output voltage, type of charge, charging mode
- display of charging current
- protection against overloads and polarity reversal.

Technical data

CODE	CODE 807540	EFFECTIVE CHARGING CURRENT	18 / 12 A	DIMENSIONS	22,5 - 29 - 20,5 cm
SINGLE PHASE MAINS VOLTAGE	230 V	RATED CHARGE CURR. EN60335-2-29	12 / 8 A	WEIGHT	7,2 kg
MAINS FREQUENCY	50 / 60 Hz	MIN. RATED REFERENCE CAPACITY	30 / 20 Ah	EAN CODE	800489764142 3
CHARGING ABSORBED POWER	300 W	MAX RATED REFERENCE CAPACITY	225 / 180 Ah	PIECES/PALLET	56 pz/pallet
CHARGING VOLTAGE	12 / 24 V	ADJUSTMENT POSITIONS	4	PIECES/PALLET - B	42 pz/pallet - B



AUTOTRONIC 25 BOOST 230V 12V/24V

Included Accessories



COLORADO 40B WORK CLAMP 40A - 712624



COLORADO 40R POSITIVE CLAMP 40A - 712623