



# T-CHARGE 26 BOOST 12V





## Overview

#### **T-CHARGE 26 BOOST 12V**

cod. 807562

Intelligent battery charger and maintainer with electronic control of the charging current, and automatic interruption and restart (PULSE-TRONIC).

Normal charge (CHARGE), automatic charge (PULSE-TRONIC) and rapid charge (BOOST), of all maintenance free, sealed batteries (GEL/AGM/START-STOP), and free electrolyte batteries (WET) with 12V voltage of motorcycles, cars, vans, tractors and boats. The CHARGE mode is advisable when the type of battery to be charged is unknown, the PULSE-TRONIC (GEL/AGM or WET) mode allows the automatic control of the battery status.

# Features:

- 3 charge current levels
- warning led for charging status, end of charge, thermostatic interruption due to short circuit of output cables or polarity reversal Supplied with three different charging cables.

## **Technical data**



CODE 807562



**EFFECTIVE CHARGING CURRENT 16 A** 



DIMENSIONS 30 - 9,5 - 5,5 cm



SINGLE PHASE MAINS VOLTAGE 230 V



RATED CHARGE CURR. EN60335-2-29 16 A



WEIGHT 1,4 kg



MAINS FREQUENCY 50 / 60 Hz



MIN. RATED REFERENCE CAPACITY 10



EAN CODE 800489773861 1



**CHARGING ABSORBED POWER 220 W** 



MAX RATED REFERENCE CAPACITY 250 Ah



PIECES/PALLET 180 pz/pallet



**CHARGING VOLTAGE 12 V** 



**ADJUSTMENT POSITIONS 3**