


# GENIUS2 6V & 12V 2A



Auto | Marine | RV | Powersport | Lawn & Garden

# NOCO genius<sup>2</sup> BATTERY CHARGER<sup>TM</sup> + MAINTAINER



## EVERYTHING CHARGER.

Do more with Genius. Multi-voltage, chemistries, and types.

Meet the GENIUS2 - Similar to our G1100, just better. It's 31% smaller and delivers over 82% more power. And it's simpler and easier to use than ever before. Plug-in, connect to the battery, select a charge mode, and start charging your battery. A fully-automatic, worry-free battery charger for year-round use. Designed for 6-volt and 12-volt lead-acid automotive, marine, and deep-cycle batteries, including flooded, gel, AGM, and maintenance-free, plus lithium-ion batteries.



### CHARGE DOWN TO ZERO VOLTS.

Charge dead batteries as low as 1-volt. Or use the all-new Force Mode that allows you to take control and manually begin charging dead batteries down to zero volts.



### BRING BATTERIES BACK TO LIFE.

Built-in desulfation mode for the most corroded batteries. Auto detection with smart diagnostic indicators starts a Repair Mode integrated within a 9-step charging profile.



### THERMAL COMPENSATION.

An integrated thermal sensor detects the ambient temperature and alters the charge to eliminate over-charging in hot climates and under-charging in cold climates.

## 24/7

### WORRY-FREE CHARGING.

Provides all-season, all-weather charging for a healthy battery. Leave plugged in 24/7 with no worries of overcharging. Automatically returns to its last selected mode.

NOCO  
30339 Diamond Parkway, #102  
Glenwillow, OH 44139 | USA  
1.800.456.6626

no.co

# NOCO<sup>®</sup>

# WHAT'S IN THE BOX.

**NOCO** Patented Technology

Patented: visit [no.co/patents](http://no.co/patents)

56" (142.24cm)



85" (217cm)

Charger +  
Interchangeable  
Connector

Battery Clamps +  
Integrated Eyelets

21"  
(55cm)



Mounting Bracket  
+ Strap




(2) #8x1"  
Self-tapping  
Screws



User Guide

## Maximum Versatility.

Genius clamps are built with needle-nose profiles for smaller terminal applications and detachable integrated eyelets for permanently mounting the accessory to the battery.



**Integrated Eyelet.**  
Directly attach to clamp or  
to battery terminal.

M6  
6mm Dia.

3.2cm

## Technical Specifications

<b>Line Voltage AC:</b>	120-240 VAC, 50-60Hz	<b>DC Cable Length:</b>	77.6 Inches
<b>Output Power:</b>	30 Watts Max	<b>AC Cable Length:</b>	71.7 Inches
<b>Charging Voltage:</b>	Various	<b>Back Current Drain:</b>	<5mA
<b>Charging Current:</b>	2A (12V), 2A (6V)	<b>Battery Capacity:</b>	Up to 40Ah, Maintains All Battery Sizes
<b>Chemistry:</b>	Lead-Acid and Lithium	<b>Housing Protection:</b>	IP65
<b>Operating Temperature:</b>	-4° to 104° F (-20° to +40° C)	<b>Dimensions (LxWxH):</b>	3.7 x 2.4 x 1.7 Inches
<b>Storage Temperature:</b>	-22° to 140° F (-30° to +60° C)	<b>Unit Weight:</b>	1.1 lbs
<b>Low-Voltage Detection:</b>	1V (12V), 1V (6V)	<b>Cooling:</b>	Natural Convection

## Charging Times

(for reference,  
results may vary)

Battery Size	Approx. Charge Time in Hours	
	6V	12V
8Ah	3	3
12Ah	4.5	4.5
18Ah	6.75	6.75
24Ah	9	9
40Ah	15	15

## What's In The Box

- Genius 2 Battery Charger w/ Interchangeable Connector
- Clamps w/ Integrated Eyelets
- Mounting Bracket w/ Strap
- (2) Self-Tapping Screws
- User Guide & Warranty Information

### Retail Packaging:

Dimensions: 3.43" x 4.25" x 6.97"  
Weight: 1.23lbs  
UPC: 0-46221-19003-8

### Inner Carton:


Dimensions: 3.70" x 4.49" x 7.20"  
Weight: 1.28lbs

### Master Carton:

Dimensions: 15.12" x 11.81" x 5.20"  
Weight: 8.44lbs  
Quantity: 6  
UCC: 10046221190035

### Units Per Pallet:

NA - 480 Units  
International - 378 Units



NOCO

30339 Diamond Parkway, #102  
Glenwillow, OH 44139 | USA  
1.800.456.6626

no.co

**NOCO**®