



LEADER 400 START 230V 12-24V



Overview

LEADER 400 START 230V 12-24V

cod. 807551

Battery charger and starter for charging free electrolyte batteries (WET) with 12/24V voltage, and starting all types of petrol-driven and diesel-driven vehicles, up to 70 hp.

Features:

- choice of normal charge, quick charge (BOOST), quick start
- display of charging and starting current
- protection against overloads and polarity reversal.



1 PH 230V



CE MARKING



EAC CERTIFICATION

Technical data

CODE	CODE 807551	EFFECTIVE CHARGING CURRENT	45 A	ADJUSTMENT POSITIONS	3
SINGLE PHASE MAINS VOLTAGE	230 V	RATED CHARGE CURR. EN60335-2-29	31 A	DIMENSIONS	26,5 x 34,5 x 23 cm
MAINS FREQUENCY	50 / 60 Hz	START CURRENT 1V/C EN60335-2-29	180 A	WEIGHT	10,9 kg
CHARGE POWER	1 KW	MAX STARTING CURRENT	300 A	EAN CODE	800489764804 0
START POWER	6,4 KW	MIN. RATED REFERENCE CAPACITY	20 A	PIECES/PALLET	27 pz/pallet
CHARGING VOLTAGE	12 / 24 V	MAX RATED REFERENCE CAPACITY	700 A	PIECES/PALLET - B	36 pz/pallet-B

Included Accessories

CABLE 10 MMQ 2 M - 123425



COLORADO 150R POSITIVE CLAMP 150A - 712002



 **LEADER 400 START 230V 12-24V**



COLORADO 150B WORK CLAMP 150A - 712001