



INFINITY 228 CE



Overview

INFINITY 228 CE

cod. 816084

MMA and TIG inverter, electrode welding machine in direct current (DC) with scratch striking. Use with a wide range of electrodes: rutile, basic, stainless steel, cast iron and cellulosic.

Features:

- compact and light
 - high welding current stability in spite of mains voltage fluctuations
 - arc force, hot start and anti-stick devices
 - thermostatic, overvoltage, undervoltage, overcurrent, motorgenerator (+/- 15%) protections.
- Complete with MMA welding accessories.



1 PH 230V



CE MARKING



EAC CERTIFICATION

Technical data

CODE	CODE 816084	A_{MAX}	MAX ABSORBED CURRENT 39 A	φ	POWER FACTOR (cosphi) 0,7
V_{1PH}	SINGLE PHASE MAINS VOLTAGE 230 V	A_{60%}	ABSORBED CURRENT AT 60% - MAX 23 A	Ø_{DC} MIN/MAX	D. USABLE ELECTRODES IN DC 1,6 - 4 mm
F	MAINS FREQUENCY 50 / 60 Hz	P_{MAX}	MAX ABSORBED POWER 6,3 kW	IP	PROTECTION DEGREE IP23
A_{MIN/MAX} DC	CURRENT RANGE 20 - 200 A	P_{60%}	ABSORBED POWER AT 60% 3,7 kW	W_H L	DIMENSIONS 40 x 14,5 x 24 cm
A_{MAX} 40°C DC	MAX CURRENT DC (EN 60974-1) 200 @ 35 % A	P_{MIN} GEN	MOTORGENERATOR MINIMUM POWER 10 kW	kg	WEIGHT 6,62 kg
A_{60%} 40°C DC	DC CURRENT 140 A	η	EFFICIENCY 90 V	BAR CODE	EAN CODE 800489798711 8
V₀ DC	MAX NO LOAD VOLTAGE 80 V				



INFINITY 228 CE

Included Accessories

CABLE - 124887

CABLE TW05V-A 1X025 02.00M PLUG ATLAS - 125033



TOLEDO 250 WORK CLAMP 250A - 712030



DALLAS 300 ELECTRODE HOLDER 300A - 712260