



TELMIG 195/2



Overview

TELMIG 195/2

cod. 821069

MIG-MAG welding machine. Designed for continuous and spot welding with electronic regulation of spotwelding time. Flexibility of use with a wide range of materials such as steel, stainless steel, high strength steels and aluminium. Thanks to optional kits this model allows also sheet tempering and riveting.

Complete with MIG-MAG welding accessories, CEE16A Schuko plug and adaptor.



1 PH 230V



CE MARKING



EAC CERTIFICATION



COIL 15 kg

Technical data

CODE 821069	DC CURRENT 80 A	ADJUSTMENT POSITIONS 8
SINGLE PHASE MAINS VOLTAGE 230 V	MAX NO LOAD VOLTAGE 53 V	STEEL WELDING WIRE DIAMETER 0,6 - 1 mm
DOUBLE PHASE MAINS VOLTAGE 400 V	MAX ABSORBED POWER 7 kW	INOX WELDING WIRE DIAMETER 0,8 mm
MAINS FREQUENCY 50 / 60 Hz	ABSORBED POWER AT 60% 2,3 kW	ALUMINIUM WELDING WIRE DIAM. 0,8 - 1 mm
CURRENT RANGE 30 - 200 A	MAINS FUSE 16 A	PROTECTION DEGREE IP21
MAX CURRENT DC (EN 60974-1) 180 @ 15 % A	POWER FACTOR (cosphi) 0,9	DIMENSIONS 80 x 45 x 57 cm

Included Accessories

CABLE 25 MMQ 1.8M - 124590



TOLEDO 250 WORK CLAMP 250A - 712030



 **TELMIG 195/2**

SPACER - 322499



ARGON GAS BOTTLE IT ADAPTOR - 432036



GAS REGULATOR REFILLABLE BOTTLE - 722341

MT15 MIG TORCH 3M (RED) - 742180