



FORCE 125



Overview

FORCE 125

cod. 815872

MMA inverter, electrode welding machine in direct current (DC).

Use with a wide range of electrodes: rutile, basic, stainless steel, cast iron, etc.

Features:

- Compact and light
 - High welding current stability in spite of mains voltage fluctuations
 - Arc force, hot start and anti-stick devices
 - Thermostatic, overvoltage, undervoltage, overcurrent, motorgenerator (+/- 15%) protections.
- Complete with MMA welding accessories and cardboard carry case.



1 PH 230V



CE MARKING



EAC CERTIFICATION

Technical data

CODE	CODE 815872	MAX ABSORBED CURRENT	15 A	D. USABLE ELECTRODES IN DC	1,6 - 2,5 mm
SINGLE PHASE MAINS VOLTAGE	230 V	MAX ABSORBED POWER	2,3 kW	PROTECTION DEGREE	IP21
MAINS FREQUENCY	50 / 60 Hz	MOTORGENERATOR MINIMUM POWER	3 kW	DIMENSIONS	32 x 37 x 14,5 cm
CURRENT RANGE	10 - 80 A	MAINS FUSE	10 A	WEIGHT	3,10 kg
%USE (20°C USE)	50% @ 80 A %	EFFICIENCY	82 V	EAN CODE	800489796980 0
MAX CURRENT DC (EN 60974-1)	80 @ 5% A	POWER FACTOR (cosphi)	0,6	PIECES/PALLET	63 pz/pallet
MAX NO LOAD VOLTAGE	72 V				



 **FORCE 125**

Included Accessories

 SLAG REMOVER - 712139

CABLE 6 MMQ 1.8 M EYELET - 713255

 DALLAS 300 ELECTRODE HOLDER 300A - 712260

- 713322