



## PULSE 30 EVO



NEW

### Overview

#### PULSE 30 EVO

cod. 807610

Multi-functional electronic battery charger, trickle charger and tester for WET, GEL, AGM, MF, PBCA, EFB, Li 12V/24V batteries with LCD display.

Charging and maintenance programs in Pulse Tronic dedicated to the technology of the selected battery. BOOST function for quick charge. Advanced function for charging and maintenance of batteries at low temperatures. Activation of the RECOVERY function enables resetting of sulphated batteries. Tests the vehicle alternator and battery. Continuous and reliable power supply source during battery changes. Simplified use and immediate display of the parameters thanks to the LCD display.

#### Features:

- Automatic charge and maintenance in Pulse Tronic based on the technology of the selected battery;
- BOOST function for quick charge of the batteries;
- COLD function to charge and maintain batteries at low temperatures;
- RECOVERY function to recover sulphated batteries;
- TEST function for battery, starting and alternator;
- SUPPLY function for stable power supply during battery changing;
- LCD display;
- Battery voltage selection;
- Protection against overcharge, short circuit and polarity reversal.

Fit with PFC device.

Complete with cables with clamps.



1 PH 230V



CE MARKING



EAC CERTIFICATION

### Technical data

<b>CODE</b>	CODE 807610	<b>A<sub>EFF</sub></b>	EFFECTIVE CHARGING CURRENT 27 / 15 A	<b>C<sub>MAX</sub></b>	MAX RATED REFERENCE CAPACITY 400 A
<b>V<sub>1PH</sub></b>	SINGLE PHASE MAINS VOLTAGE 230 V	<b>A<sub>EN</sub></b>	RATED CHARGE CURR. EN60335-2-29 25 / 12 A	<b>IP</b>	PROTECTION DEGREE IP33



## PULSE 30 EVO



MAINS FREQUENCY 50 / 60 Hz



START CURRENT 1V/C EN60335-2-29  
25 (Boost) A



DIMENSIONS 9,2x20x33 cm



CHARGING ABSORBED POWER 369 W



MIN. RATED REFERENCE CAPACITY 5  
Ah



WEIGHT 3,11 kg



CHARGING VOLTAGE 12 / 24 V

---

### Included Accessories

CLAMPS PATCH CORD - 125277